

The natural choice for small businesses who demand the finest quality in print.

i-SENSYS
LBP7100Cn

i-SENSYS
LBP7110Cw

you can



Stylish laser printer with Wi-Fi*. Ideal for small businesses who need consistent high quality print.

This compact A4 laser printer offers up to 14ppm in both colour and black and white. With built-in Wi-Fi*, it's the ideal choice for small businesses who want consistent, high quality results.

Key features

- Professional-quality A4 colour laser printer
- Sleek, low profile design blends easily into small business environments
- Ideal for personal use or for sharing via the network in small workgroups
- 14ppm for both mono and colour helps keep productivity high
- Up to 1200 x 1200 dpi print resolution
- 150-sheet paper cassette
- Wi-Fi* connectivity ensures it can be shared easily
- No waiting with Quick First-Print technologies
- Quiet and energy efficient
- Convenient, easy-to-use All-in-One cartridge

What's in the box

Main unit, 731 C/M/Y/K starter cartridge, power cord, starter guide, wireless set-up guide* and warranty card with user software and manual CDs.

Dimensions (W x D x H)

406mm x 454mm x 255mm

Supported OS

Windows XP (32bit/64bit) / Vista (32bit/64bit) / 7 (32bit/64bit) / Server 2003 (32bit/64bit) / Server 2008 (32bit/64bit) / Server 2008 R2 (64bit)

Mac OS 10.5.x and up (Web distribution only)

Linux (Web distribution only)

Citrix



PRINT



COPY



FAX



SCAN

* LBP7110Cw only

Canon

i-SENSYS
LBP7100Cn

i-SENSYS
LBP7110Cw



- 1 150-sheet cassette
- 2 Cartridge 731:
5 cartridges available: Cyan, Magenta, Yellow, Black and Black H

Specifications:

PRINTER ENGINE	<p>Print speed Up to 14ppm colour (A4) Up to 14ppm mono (A4)</p> <p>Printing method Colour laser beam printing</p> <p>Print quality Up to 1200 x 1200 dpi</p> <p>Print resolution Up to 600 x 600 dpi</p> <p>Warm-up time Approx. 20 seconds or less from power on</p> <p>First Page Out Time Mono: Approx. 18 seconds or less Colour: Approx. 18 seconds or less</p> <p>Duty cycle Max. 30,000 pages per month¹</p> <p>Print margins 5mm – top, bottom, left and right</p>
MEDIA HANDLING	<p>Paper input (Standard) 150-sheet cassette</p> <p>Paper output 125-sheet face down</p> <p>Media types Plain paper, Heavy Paper, Transparency, Coated Paper, Glossy film, Label, Index card, Envelope</p> <p>Media sizes Cassette: A4, B5, A5, Legal, Letter, Executive, Statement, Foolscap, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Index Card, Custom sizes: Width: 83.0mm to 215.9mm; Length: 127.0mm to 355.6mm</p> <p>Media weights Cassette: 60 to 220 g/m²</p>
GENERAL FEATURES	<p>Power requirements 220-240V (±10%) 50/60Hz (±2Hz)</p> <p>Power consumption Maximum: Approx. 800 W or less Active: Approx. 340 W or less Standby: Approx. 10 W Sleep mode: Approx. 0.9 W² Typical Electricity Consumption (TEC): 1.0 kWh/week</p> <p>Noise level Sound power³: Active: 6.52 B or less Standby: Inaudible Sound pressure³: Active: 49 dB(A) or less Standby: Inaudible</p> <p>Dimensions (W x D x H) 406mm x 454mm x 255mm</p> <p>Weight Approx. 16.6kg</p> <p>Operating environment Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)</p> <p>Control panel 12 LED indicators⁴ 4 Operation keys</p>

CONTROLLER	<p>Memory 64 MB</p> <p>Printer languages UFR II-LT</p> <p>Interface and connectivity USB 2.0 High-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g⁵</p> <p>Software and printer management MF/LBP Network Setup Tool, Remote User Interface (RUI)</p> <p>Operating systems compatibility Windows XP (32bit/64bit) / Vista (32bit/64bit) / 7 (32bit/64bit) / Server 2003 (32bit/64bit) / Server 2008 (32bit/64bit) / Server 2008 R2 (64bit) Mac OS 10.5 and up⁶ Linux⁶ Citrix</p>
CONSUMABLES	<p>All-in-One cartridges Cartridge 731 Black (1,400 pages⁷)⁸ Cartridge 731H Black (2,400 page⁷)⁸ Cartridge 731 Cyan (1,500 pages⁷)⁸ Cartridge 731 Magenta (1,500 pages⁷)⁸ Cartridge 731 Yellow (1,500 pages⁷)⁸</p>
<p>Standard disclaimers. All specifications subject to change without notice.</p> <p>1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product</p> <p>2] When LBP7110Cw is in wireless mode, consumption will be 4 W</p> <p>3] Declared noise emission in accordance with ISO 9296</p> <p>4] The LBP7100Cn has 11 LED indicators</p> <p>5] LBP7110Cw only</p> <p>6] Web distribution only. The driver will be released April 2013</p> <p>7] Based on ISO/IEC19798</p> <p>8] Printer ships with 800-page starter cartridges</p>	



Canon Inc
canon.com

Canon Europe
canon-europe.com

European Edition
© Canon Europa N.V.,
2012

Canon