




The Shape that Fits the Future

DC3217IYE



only
4" x 4"

PRODUCT BRIEF

Introducing Intel's Next Unit
of Computing Kit DC3217IYE

THINK YOU KNOW WHAT SMALL CAN DO? THINK AGAIN.

No more compromising between performance, profile, and price. The Next Unit of Computing (NUC) is a tiny 4"×4"×2" computing device with the power of the 3rd generation Intel® Core™ i3 processor. Its lower power consumption enables innovative system designs and energy-efficient applications in places like digital signage, home entertainment, and portable uses.

SUPERIOR PROCESSING AND GRAPHICS

Visibly smart graphics using the 3rd generation Intel® Core™ i3-3217U processor deliver amazing performance and visually stunning graphics.



STUNNINGLY SMALL FORM FACTOR

The 4"×4"×2" form factor unlocks a world of potential design applications, from digital signage and kiosks to portable innovations.

ADVANCED TECHNOLOGY

The NUC features two SO-DIMM sockets for expandability upto 16 GB of memory, two PCIe* mini-card connectors for flexible support of wireless and SSD configurations, BIOS vault technology, fast boot and the Intel® Visual BIOS. The NUC also supports The Intel® Anti-Theft™ Technology providing hardware intelligence designed to protect your device and its data if its lost or stolen.

Integrated Board	<ul style="list-style-type: none">• D33217GKE
Dimensions	<ul style="list-style-type: none">• 116.6mm×112.0mm×39.0mm (4.59"×4.41"×1.55")
Cooling	<ul style="list-style-type: none">• Active
Drive options	<ul style="list-style-type: none">• mSATA
Color options	<ul style="list-style-type: none">• Black only
Chassis design	<ul style="list-style-type: none">• Aluminum and Plastic
Power Supply	<ul style="list-style-type: none">• 19V, 65W DC-DC power adapter
Additional Features	<ul style="list-style-type: none">• Antenna for WIFI and Bluetooth pre-assembled for ease of deployment• Front Panel USB 2.0• VESA mounting bracket included• Integration Guide• 3 year Product Life Cycle



Full PC functionality in its simplest form

...with Intel® Desktop Board D33217GKE

Intel® Gigabit Ethernet

Dual HDMI ports supporting dual independent display capability

Dual USB 2.0 Ports

19V, 65W DC Power connector




Dual Mini PCIe slots for expandability

Front Panel USB 2.0 Port



Dual SO-DIMM sockets for memory expandability upto 16 GB

Intel® QS77 Express chipset



Intel® Core™ i3-3217U processor



Intel® Next Unit of Computing Kit DC3217IYE

Technical Specifications



PROCESSOR

Processor Support

- Intel® Core™ i3 3217U Processor (1.8 GHz, Dual Core processor with 3 MB smart cache)
- Supports Intel® 64 architecture³

CHIPSET

- Intel® QS77 Express Chipset

GRAPHICS

- Intel® HD Graphics 4000
- Dual HDMI Ports supporting dual independent display capability

PERIPHERAL CONNECTIVITY

- Integrated Intel 10/100/1000 Network Connection
- Three Hi-Speed USB 2.0 ports (two back panel ports and one front panel port)

EXPANSION CAPABILITIES²

- One full length mini-PCIe slot supporting mSATA capability
- One half length mini-PCIe slot with dual USB 2.0 ports routed

SYSTEM BIOS

- Intel® Visual Bios
 - 64 Mb Flash EEPROM with Intel® Platform Innovation Framework for EFI Plug and Play
 - Advanced configuration and power interface V3.0b, SMBIOS2.5
 - Intel® Express BIOS update support
- Fast Boot BIOS - Optimized POST for almost instant-on access to PC from power on**

SYSTEM MEMORY¹

Memory Capacity

- Dual-channel DDR3 with two connectors for 1333/1600 MHz memory support (16 GB max)

Memory Voltage

- 1.5V and 1.35V

HARDWARE MANAGEMENT FEATURES

- Processor fan speed control
- Voltage and temperature sensing
- Fan sensor inputs used to monitor fan activity
- ACPI-compliant power management control

INTEL® PRO 10/100/1000 NETWORK CONNECTION

- Low-power design

AUDIO

- Intel® High Definition Audio (Intel HD Audio) via two HDMI 1.4a outputs supporting 8 channel (7.1) digital audio

INDICATORS AND CONTROLS

- HDD LED, Power LED
- Power on/off

MECHANICAL

Chassis Size

- 4.59"×4.41"×1.55" (116.6mm×112.0mm×39.0mm)

Board Size

- 4"×4" (101.6mm×101.6mm)

Baseboard Power Requirements

- DC Power 19V, 65 Watt

ENVIRONMENT

Operating Temperature

- 0°C to +55°C

Storage Temperature

- -20°C to +70°C

COMPLIANCE WITH REGULATIONS AND STANDARDS

Safety Regulations

- UL/CSA 60950-1
- EN 60950-1
- IEC 60950-1
- NOM-019-SCFI-1998
- GOST-R

EMC Class B Regulations

- CISPR 22
- CISPR 24
- FCC 47 CFR Part 15, Subpart B
- ICES-003
- EN 55022
- EN 55024
- EN 61000-3-2
- EN 61000-3-3
- IEC/EN 61000-4 Series
- VCCI V-3
- KN-22
- KN-24
- CNS 13438

ENVIRONMENTAL COMPLIANCE

- Europe RoHS
- China RoHS

¹ WARNING: Altering PC memory frequency, voltage and/or latency may: (i) reduce system stability and useful life of the system, memory and processor; (ii) cause the processor and other system components to fail; (iii) cause reductions in system performance; (iv) cause additional heat or other damage; and (v) affect system data integrity. Intel has not tested, and does not warrant, the operation of the memory beyond its specifications. Intel assumes no responsibility that the memory, including if used with altered clock frequencies and/or voltages, will be fit for any particular purpose. Check with memory manufacturer for warranty and additional details.

² System resources and hardware (such as PCI and PCI Express*) require physical memory address locations that can reduce available addressable system memory. This could result in a reduction of as much as 1 GB or more of physical addressable memory being available to the operating system and applications, depending on the system configuration and operating system.

³ 64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers, and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See <http://developer.intel.com/technology/intel64/index.htm> for more information.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT.

Intel products are not intended for use in medical, life-saving, or life-sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice.

All products, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Availability in different channels may vary.

Actual Intel® Desktop Board may differ from the image shown.

Requires an Intel® WiDi enabled system and Intel WiDi enabled receiver device. 1080p and Blu-ray* or other protected content playback only available on 2nd or 3rd gen Intel® Core™ processor-based PCs with built-in visuals enabled, a compatible receiver device and media player, and supporting Intel WiDi software and graphics driver installed. Consult your PC manufacturer. For more information, see www.intel.com/go/widi.

Intel, the Intel logo, Intel Core, Pentium, and Celeron are trademarks of Intel Corporation in the U.S. and other countries.

* Other names and brands may be claimed as the property of others.

Copyright © 2012 Intel Corporation. All rights reserved.

09/12/FH/MED/PDF 327984-001US

